



## SUPER W1 Heavy-duty Clamp

Mikalor was the first company to design and produce a heavy-duty hose clamp, capable of ensuring leaktightness in high-pressure applications.

The high strength 8.8 grade steel nut and T-bolt mean that Super can be tightened up hard using many kinds of tools, while the bevelled edges protect the hose from harm.

The Super clamp is in its element in agricultural applications, wastewater extraction, mining, quarrying or in other sectors where a rugged yet competitively priced heavy-duty clamp is required.

*\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø										
d mm	Part n°	r	e	a	b	s	Maximum values		Box Quantity (M00)	Outer Packing
							Torque (Nm)	Pressure(Bars)		
17-19	0301826-3	M5	8	18 <sup>+02</sup>	19,8	0,6	4,5	48	50	400
20-22	0301827-1	M5	8	18 <sup>+02</sup>	19,8	0,6	4,5	48	50	400
23-25	0301828-0	M5	8	18 <sup>+02</sup>	19,8	0,6	4,5	45	50	400
26-28	0301829-8	M5	8	18 <sup>+02</sup>	19,8	0,6	4,5	45	50	400
29-31	0301830-0	M6	10	20 <sup>+03</sup>	22	0,8	8	42	50	50
32-35	0301831-9	M6	10	20 <sup>+03</sup>	22	0,8	8	42	50	50
36-39	0301832-7	M6	10	20 <sup>+03</sup>	22	0,8	8	40	50	50
40-43	0301833-5	M6	10	20 <sup>+03</sup>	22	0,8	8	40	50	50
44-47	0301801-0	M7	11	22 <sup>+02</sup>	24,5	1,2	16	44	50	50
48-51	0301802-8	M7	11	22 <sup>+02</sup>	24,5	1,2	16	44	50	50
52-55	0301803-6	M7	11	22 <sup>+02</sup>	24,5	1,2	16	40	25	25
56-59	0301804-4	M7	11	22 <sup>+02</sup>	24,5	1,2	16	40	25	25
60-63	0301805-2	M7	11	22 <sup>+02</sup>	24,5	1,2	16	36	25	25
64-67	0301806-0	M7	11	22 <sup>+02</sup>	24,5	1,2	16	36	25	25
68-73	0301807-9	M8	13	24 <sup>+04</sup>	26,5	1,5	25	28	25	25
74-79	0301808-7	M8	13	24 <sup>+04</sup>	26,5	1,5	25	28	25	25
80-85	0301809-5	M8	13	24 <sup>+04</sup>	26,5	1,5	25	28	25	25