

TRADEFLEX

Excellent flexibility at low temperature. A hose for the transfer of air, water and ideal for the tradesperson as an air compressor hose. Blue smooth outer cover with a black inner wall.

UV stabilised > Conforms to AS 2554 Class B > Temperature range: 0°C to 60°C > * Supplied on wooden reels



CAC CHEMAIR AIRLINE

Premium lightweight flexible airline hose. The added benefit of a chemical resistant tube makes it suitable for low pressure agriculture spray applications.



P

# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
CAC-006-***	6	12	250	60	20 100 300#
CAC-008-***	8	14	250	70	20 100 300#
CAC-010-***	10	17	290	85	20 30 100 200#
CAC-012-***	12.5	19	250	95	20 100 200#
CAC-020-***	20	27.5	250	190	20 100

Common Applications:

- Rattle Guns
- Nail Guns
- Pneumatic Tools
- Ag Spray

HAL BLUE ADFLEX AIRLINE

Flexible lightweight airline hose. It provides an economical alternative for users who do not require the higher working pressure of 10mm Chemair.



P

# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
HAL-010-***	10	16	250	85	20 100 300#

Common Applications:

- Pneumatic Tools
- Portable Equipment

BSW BLUE STRIPE WASHDOWN

Premium washdown hose designed specifically for cold washdown applications. Its distinctive white cover with blue stripe is smooth for ease of handling and its virgin PVC construction ensures unmatched performance, flexibility and service life.



P

# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
BSW-020-***	20	28	145	140	20 50 100
BSW-025-***	25	33	145	180	20 50 100
BSW-032-***	32	42	145	210	20 40 100

Common Applications:

- Golf Courses
- Bowling Greens
- Dairy's
- Parks and Gardens

NTP PETROL RESISTANT/FOOD CONTACT

Translucent dual purpose food contact/petrol hose with a distinctive red/gold tracer to identify its dual application. Conforms to AS/NZS 2070 for food contact requirements.



P

# Part Number	ID (mm)	OD (mm)	WP (mm)	BR (mm)	Coil Length (metres)
NTP-006-***	6	12	250	65	20 100 300#
NTP-008-***	8	14	250	75	20 100 300#
NTP-010-***	10	16	250	85	20 100 200#
NTP-012-***	12.5	19	250	100	20 100 200#
NTP-016-***	16	22	250	130	20 100
NTP-020-***	20	27.5	250	150	20 50 100
NTP-025-***	25	33	250	180	20 50 100
NTP-032-***	32	42	145	220	10 20 40
NTP-038-***	38	49	145	250	10 20 40
NTP-050-***	50	63	145	320	10 20 40

Common Applications:

- Air Lines
- Water Transfer
- Transfer Line in Food Processing
- Petroleum Products
- Siphon Lines

CVT CLEAR VINYL TUBING

Suitable for food and beverage lines operating at low pressures, general purpose low pressure delivery lines, light siphon lines, cable protection and drainage lines. Conforms to AS/NZS 2070 for food contact requirements.



T

# Part Number	ID (mm)	OD (mm)	WP (psi)	BR (mm)	Coil Length (metres)
CVT-003-***	3	5	NA	50	30
CVT-005-***	5	8	NA	55	30 100*
CVT-006-***	6	9	NA	65	30 100*
CVT-008-***	8	11	NA	75	30 90*
CVT-010-***	10	13	NA	85	30 100*
CVT-012-***	12.5	15.5	NA	100	30 80*
CVT-016-***	16	19	NA	130	30
CVT-020-***	20	24	NA	150	30
CVT-025-***	25	30	NA	180	30
CVT-032-***	32	38	NA	220	30
CVT-038-***	40	47	NA	250	15 30
CVT-050-***	50	58	NA	320	15 30

Common Applications:

- Siphon Lines
- Cable Protection
- Drainage Lines
- Food and Beverage Transfer Lines



POWAFLEX BOSS BLUE PREMIUM PVC SUCTION HOSE

BOSS blue premium PVC suction hose is a robust suction hose suitable for diesel fuel, oil and oil based fluids and chemical resistant.
> Temperature range: -10°C to +60°C.

PFX PUMPFLEX

For conveying water, other liquids and light granular materials. Suitable for agriculture and industrial applications.



SD

# Part Number	ID (mm)	OD (mm)	UHg Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
PFX-025-***	25.5	31.9	600	75	20
PFX-032-***	32.2	39.0	600	115	20
PFX-038-***	38.5	46.1	600	160	20 30
PFX-050-***	51.2	59.6	600	220	20 30
PFX-063-***	64.4	74.0	600	320	20
PFX-075-***	76.1	87.2	600	360	20 30
PFX-100-***	102.1	114.2	675	570	6 10 20 [C]
PFX-125-***	127.8	141.4	675	800	6 10 20 [C]
PFX-150-***	153.4	169.8	675	1100	6 10 20 [C]

Common Applications:

- Fire fighter pumps
- Water Suction
- General Industry
- Construction Site De-watering



POWAFLEX METALLIC BLUE SUPER ELASTIC PVC OIL SUCTION HOSE

An **extra flexible** hose offering excellent bending radius and kink resistance. Suitable for oil and oil based fluids, diesel fuel and chemical resistant. > Temperature range: -10°C to +60°C.

HSC

PLUTONE CLEAR/STEEL WIRED REINFORCED

Suitable for applications requiring continuous bending and flexing, or where a clear, heavy duty hose is needed. Ideal for food and beverage contact. Conforms to CE 1935/2004 for use with food-stuffs – liquids, dry and alcohol.



SD

# Part Number	ID (mm)	OD (mm)	Ug Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
HSC-006-***	6	12	699	13	60
HSC-008-***	8	14	699	16	60
HSC-010-***	10	16	625	18	20 60
HSC-012-***	12	18	625	23	20 60
HSC-016-***	16	22.4	625	30	30 60
HSC-020-***	20	27	625	34	20 60
HSC-025-***	25	33	625	42	20 30
HSC-032-***	32	41	625	53	30
HSC-038-***	38	47	625	63	30
HSC-050-***	50	60	588	82	30
HSC-063-***	63	75	588	138	30
HSC-075-***	76	89	515	164	20 30
HSC-100-***	102	116	515	215	30 [C]

Common Applications:

- Food and Beverage Transfer
- Salt and Fresh Water Lines
- Chemical
- Foaming Units
- Light Slurries

CMX

CELLARMAX

For non-toxic applications requiring a heavy duty hose. Suitable for wine and fruit juice. Conforms to AS/NZS 2070 standards. Winery/food contact clear with red helix.



SD

# Part Number	ID (mm)	OD (mm)	Ug Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
CMX-025-***	25.5	33.1	735	70	20
CMX-032-***	32.2	40.2	735	110	20
CMX-038-***	38.5	46.9	735	150	20
CMX-050-***	51.2	60.2	735	200	20
CMX-063-***	64.4	75.2	720	290	20
CMX-075-***	76.2	87.4	720	350	20
CMX-100-***	102.2	115.0	675	570	20
CMX-125-***	127.8	141.8	675	760	20

Common Applications:

- Wine transfer
- Food Processing
- Beverage Lines

OFX

OILFLEX

For conveying petroleum products and derivatives, lubricating oils and various chemicals and sludge. Heavy duty oil suction blue. Made with Thermoplastic rubber for improved flexibility and durability.



SD

# Part Number	ID (mm)	OD (mm)	Ug Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
OFX-025-***	25.5	33.5	675	60	20
OFX-032-***	32.2	40.6	675	95	20
OFX-038-***	38.5	47.5	675	120	20
OFX-050-***	51.2	61.2	675	180	20
OFX-063-***	64.4	75.4	675	280	20
OFX-075-***	76.2	87.6	675	340	20
OFX-100-***	102.2	115.2	675	560	20

Common Applications:

- Sludge Pumping
- Grease Pit Tankers
- Marine Plumbing
- Plumbing Potable Toilets
- Diesel Tankers

CFX CROPFLEX

This extremely flexible medium duty hose is suitable for suction and low pressure delivery. For use on agricultural and chemical spraying equipment, suction and discharge on environmental waste collection tankers and in water transfer applications.



S.D

# Part Number	ID (mm)	OD (mm)	UHg Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
CFX-025-***	25.5	31.9	130	70	20
CFX-032-***	32.2	39.0	120	100	20
CFX-038-***	38.5	46.5	105	150	20
CFX-050-***	51.2	59.6	95	200	20

- Common Applications:**
- Crop Spray
 - Horticultural Equipment
 - Waste Collection

HVA VACBEAST II ANTI-STATIC SLURRY HOSE

New Improved anti-static hose for vacuum waste recovery and heavy duty suction applications where flexibility is important. Widely used on tank trucks or as an oil recovery hose.



S.D

# Part Number	ID (mm)	OD (mm)	UHg Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
HVA-050-***	52	63	600	180	20 30
HVA-063-***	63	75	600	230	20 30
HVA-075-***	76	89	600	290	20 30
HVA-100-***	102	118	600	380	10 30 [C]
HVA-125-***	127	145	525	500	30
HVA-150-***	152	172	525	630	10 20 [C]
HVA-200-010	203	229	450	900	10

- Common Applications:**
- Industrial Vacuum Units
 - Tank Truck Recovery
 - Abrasive Suction

LF3 SUNNY BRICK RED HEAVY DUTY

A premium quality heavy duty layflat. The excellent abrasion resistance allows it to be used in heavy de-watering applications.



L

# Part Number	ID (mm)	OD (mm)	WP (psi)	BR (mm)	Coil Length (metres)
LF3-038-***	40	NA	150	NA	50 100
LF3-050-***	52.5	NA	150	NA	50 100
LF3-063-***	66	NA	150	NA	50 100
LF3-075-***	78.5	NA	130	NA	50 100
LF3-100-***	104	NA	130	NA	50 100 [C]
LF3-150-***	155	NA	100	NA	50 100 [C]
LF3-200-***	207	NA	70	NA	100

- Common Applications:**
- Pit De-Watering
 - Quarries
 - Industrial Washdown
 - Building Sites

LF1 SUNNY BLUE LOW PRESSURE

Light duty layflat hose produced by the world leading manufacturer Sunny Hose. This hose can be pierced without delamination as it is constructed with one layer ensuring its suitability for trickle irrigation applications.



L

# Part Number	ID (mm)	OD (mm)	WP (psi)	BR (mm)	Coil Length (metres)
LF1-038-***	41	NA	75	NA	50 100
LF1-050-***	53	NA	65	NA	50 100
LF1-063-***	66	NA	60	NA	50 100
LF1-075-***	78	NA	50	NA	50 100
LF1-100-***	104	NA	45	NA	50 100
LF1-150-***	155	NA	45	NA	50 100 [C]
LF1-200-***	207.5	NA	45	NA	50 100 [C]

- Common Applications:**
- Construction Sites
 - Trickle Irrigation